



Shown without splash guard

Brief description:

Powerful one-hand polisher with constant electronic speed control.

Special features:

- For special work: Short design with strong motor.
- Proven, flexible and transparent splash guard. This means that less moisture and dirt is sucked into the engine compartment. This significantly increases the service life of the machine.
- Water-cooled Aluminium end shield.
- Wear-resistant and unbreakable silicone power cable in signal colour (clearly visible).
- Soft start and electronics for constant speed even under load.
- Temperature-dependent overload protection.
- Spindle lock for easy tool changes.
- Speed range designed for stone polishing with infinitely variable speed regulation.
- Special requests (e.g. for longer connecting cables or hoses) can be considered.
- Repair service for all of our machines.

Application:

Wet polisher for natural or artificial stone processing. Especially suitable for stonemasons, sculptors, restorers, tilers, renovators, floor renovators, etc.

Technical Data:


| | | | |
|--------------|------------|---------------------|--------|
| Voltage: | 230 Volt | Spindle thread: | M 14 |
| Power: | 1,420 Watt | Weight: | 2.9 kg |
| Speed: | 2,500 rpm | Soft start | |
| Tool Ø max.: | 100 mm | Overload protection | |

Included:

Silicone connecting cable 4 m, hose 2.5 m with brass quick coupling, bail handle, personal protection switch PRCD or CEE-plug, splash guard, carton.

Available versions:

| | | | |
|----------------------|-------------------|------|-----------------------|
| POLIFOX 1400 Con DI | (with PRCD) | 230V | Item-no.: 004.003.130 |
| POLIFOX 1400 Con CEE | (for transformer) | 230V | Item-no.: 004.003.131 |



Rinsing head spindle bearing

GALESKI Quality:

Spindle mounting in rinsing head, with water sealing underneath.

With transparent, flexible splash guard.
Advantage: Less moisture and dirt gets into the machine.
(Shown: Polifox 1700)

