



Shown without splash guard

Brief description:

Ideal starter machine – inexpensive, has variable speed regulation.

Special features:

- Proven, flexible and transparent splash guard. This means that less moisture and dirt is sucked into the engine compartment. This significantly increases the service life of the machine.
- Water-cooled Aluminium end shield.
- Wear-resistant and unbreakable silicone power cable in signal colour (clearly visible).
- Soft start and electronics for constant speed even under load.
- Temperature-dependent overload protection.
- Spindle lock for easy tool changes.
- Speed range designed for stone polishing with infinitely variable speed regulation.
- 2 service ports for easy replacements of the carbon brushes.
- Bail handle and ergonomic rear handle for safe and comfortable work.
- Special requests (e.g. for longer connecting cables or hoses) can be considered.
- Repair service for all of our machines.

Application:

Wet polisher for natural or artificial stone processing. Especially suitable for stonemasons, sculptors, restorers, tilers, renovators, floor renovators, etc.

Technical Data:


Voltage:	230 / 115 Volt	Spindle thread:	M 14
Power:	1,400 Watt	Weight:	2.9 kg
Speed:	900 - 3,400 rpm	Soft start	
Tool-Ø max.:	100 mm	Overload protection	

Included:

Silicone connecting cable 4 m, hose 2.5 m with brass quick coupling, bail handle, personal protection switch PRCD or CEE-plug, splash guard, carton.

Available versions:

POLIFOX 1400 Vario DI	(with PRCD)	230V	Item-no.: 004.003.132
POLIFOX 1400 Vario CEE	(for transformer)	230V	Item-no.: 004.003.133
POLIFOX 1400 Vario DI	(with PRCD)	115V	Item-no.: 004.003.134
POLIFOX 1400 Vario CEE	(for transformer)	115V	Item-no.: 004.003.135



Rinsing head spindle bearing

GALESKI Quality:

Spindle mounting in rinsing head, with water sealing underneath.

With transparent, flexible splash guard.
Advantage: Less moisture and dirt gets into the machine.
(Shown: Polifox 1700)

