



Shown without splash guard

## Brief description:

Compact and easy to handle for light polishing jobs, has constant electronic speed control.

## Special features:

- Light machine - also suitable for one-handed use.
- Proven, flexible and transparent splash guard. This means that less moisture and dirt is sucked into the engine compartment. This significantly increases the service life of the machine.
- Water-cooled Aluminium end shield.
- Soft start and electronics for constant speed even under load.
- Temperature-dependent overload protection.
- Spindle lock for easy tool changes.
- Speed range designed for stone polishing.
- Special requests (e.g. for longer connecting cables or hoses) can be considered.
- Repair service for all of our machines.

## Application:

Wet polisher for natural or artificial stone processing. Especially suitable for stonemasons, sculptors, restorers, tilers, renovators, floor renovators, etc.

## Technical Data:


Voltage:	230 Volt	Spindle thread:	M 14
Power:	890 Watt	Weight:	2.3 kg
Speed:	3,400 rpm	Soft start	
Tool Ø max.:	100 mm	Overload protection	

## Included:

Rubber connecting cable 4 m, hose 2.5 m with brass quick coupling, bail handle, personal protection switch PRCD or CEE-plug, splash guard, carton.

## Available versions:

POLIFOX 900 CON DI	(with PRCD)	230V	Item-no.: 004.003.121
POLIFOX 900 CON CEE	(for transformer)	230V	Item-no.: 004.003.122



### Rinsing head spindle bearing

*GALESKI Quality:*

Spindle mounting in rinsing head, with water sealing underneath.



Also suitable for one-handed use.

