



The autbalancer consists of steel balls, lubricated in oil, that freely move around the drive shaft in a housing similar to that for ball bearings, and so perfectly level out any imbalance.



Suction hood with spring-loaded brush ring and hinged front opening.



Brief description:

Powerful motor and high quality gear unit for hard continuous use at low speed. Ergonomic bail handle and autobalancer reduce work fatigue.

Special features:

- Optimum dust extraction through suction hood with spring-loaded brush ring.
- Safety front opening for working close to the wall.
- Aluminium end shield with excellent heat dissipation.
- Autobalancer for correction of imbalances.
- Soft start and electronics for constant speed even under load.
- Temperature-dependent overload protection.
- Spindle lock for easy tool changes.
- Wide speed range with infinitely variable speed regulation.
- 2 service ports for easy replacements of the carbon brushes.
- Wear-resistant and unbreakable silicone power cable in signal colour (clearly visible).
- Bail handle and ergonomic rear handle for safe and comfortable work.
- Special requests (e.g. for longer connecting cables or hoses) can be considered.
- Repair service for all of our machines.

Application:

Dry grinder for natural or artificial stone processing. Especially suitable for stonemasons, sculptors, restorers, tilers, renovators, floor renovators, etc.

Technical Data:

Voltage:	230 Volt	Spindle thread:	M 14
Power:	1,750 Watt	Weight:	4.5 kg
Speed:	1,700 - 6,800 rpm	Soft start	
Tool-Ø max.:	125 mm	Overload protection	

Included:

Silicone connecting cable 4 m, bail handle, autobalancer, twin hole wrench, flange nut, hose connector, hose adapter 40 cm long, spring loaded brush ring with foldable front flap, case.

Available versions:

TORNADO 125 MAXI Vario	230V	Item-no.: 003.036.123
TORNADO 125 MAXI Vario	115V	Item-no.: 003.036.129