



Suction hood with spring-loaded brush ring and hinged front opening.

## Brief description:

Professional machine for beginners with spring-loaded brush ring. Foldable front flap and constant electronic speed control. High-quality gear for robust continuous operation.

## Special features:

- Optimum dust extraction through suction hood with spring-loaded brush ring.
- Safety front opening for working close to the wall.
- Aluminium end shield with excellent heat dissipation.
- Soft start and electronics for constant speed even under load.
- Temperature-dependent overload protection.
- Spindle lock for easy tool changes.
- 2 service ports for easy replacements of the carbon brushes.
- Wear-resistant and unbreakable silicone power cable in signal colour (clearly visible).
- Special requests (e.g. for longer connecting cables or hoses) can be considered.
- Repair service for all of our machines.

## Application:

Dry grinder for natural or artificial stone processing. Especially suitable for stonemasons, sculptors, restorers, tilers, renovators, floor renovators, etc.

## Technical Data:

Voltage:	230 Volt	Spindle thread:	M 14
Power:	1,500 Watt	Weight:	4.5 kg
Speed:	9,500 rpm	Soft start	
Tool Ø max.:	125 mm	Overload protection	

## Included:

Silicone connecting cable 4 m, side handle, twin hole wrench, flange nut, hose connector, hose adapter 40cm long, spring loaded brush ring with foldable front flap, carton.

## Available versions:

TORNADO 125 SPEED Con	230V	Item-no.: 003.036.120
TORNADO 125 SPEED Con	115V	Item-no.: 003.036.126