

Pulling cut: Tilting movement over the guide edge with simultaneous good suction performance.



PREMIUM QUALITY MADE IN GERMANY

# • As well as ensuring a clear view of the cutting area, the guard and suction

- To make a right-angled cut, place the bottom edge of the suction nozzle (guide edge) on the stone, set the running disc into the stone (using a tilting motion over the guide edge), and following the guide edge, make the cut.
- Soft start and electronics for constant speed even under load.
- Temperature-dependent overload protection.
- Spindle lock for easy tool changes.
- Speed range designed for stone cutting with infinitely variable speed regulation.
- Wear-resistant and unbreakable silicone power cable in signal colour (clearly visible).
- Special requests (e.g. for longer connecting cables) can be considered.
- · Repair service for all of our machines.

# **Application:**

Dry stone cutter for natural or artificial stone processing. Especially suitable for stonemasons, sculptors, restorers, tilers, renovators, floor renovators, etc.

# **Technical Data:**

M 14 / 22,2 mm Voltage: 230 Volt Spindle / Borehole: Power: 1,520 Watt Weight: 2.0 kg

Speed: 2,700 - 9,500 rpm Soft start

Tool Ø max.: 125 mm Overload protection

Cutting depth max. 25 mm

#### Included:

Silicone connecting cable 4 m, vacuum cleaner connection rotatable Ø 36-46 mm, flange, flange nut, twin hole wrench, ball handle, carton.

## **Available versions:**

SMART CUTTER 125 Vario Eco 230V Item no.: 003.036.606 487.00 €

### **GALESKI - Manufaktur innovativer Maschinen**

Boschstr. 4 • D-56457 Westerburg Tel.: +49 2663 9437-0 • Fax: +49 2663-9437-37 E-Mail: info@galeski.de • Web: www.galeski.de