

Data sheet

SMART CUTTER 1700 Vario Plus

Dry stone cutter





The guide plate can easily be removed for freehand cutting.

Brief description:

Swivel joint for the

Vacuum cleaner connection

Easy to handle stone cutter for the pulling cut, with guard and vacuum cleaner connection. The guide is removable, making the machine much more versatile.

Special features:

- Powerful freehand machine with vacuum cleaner connection, which is additionally
 equipped with a guide plate and lateral stop. This makes the SMART CUTTER even more
 versatile (see picture sequence Application 1-4).
- As well as ensuring a clear view of the cutting area, the guard and suction nozzle provide excellent dust extraction.
- To make a right-angled freehand cut without guide plate, place the bottom edge of the suction nozzle (guide edge) on the stone, set the running disc into the stone (using a tilting motion over the guide edge), and following the guide edge, make the cut (Application 1).
- · Spindle lock for easy tool changes.
- · FIXTEC quick-change system for toolless disc change.
- Soft start and electronics for constant speed even under load.
- · Temperature-dependent overload protection.
- Speed range designed for stone cutting with infinitely variable speed regulation.
- Wear-resistant and unbreakable silicone power cable in signal colour (clearly visible).
- Special requests (e.g. for longer connecting cables) can be considered.
- · Repair service for all of our machines.

Application:

Dry stone cutter for natural or artificial stone processing. Especially suitable for stonemasons, sculptors, restorers, tilers, renovators, floor renovators, etc.

Technical Data:

 Voltage:
 230 Volt
 Spindle / Borehole:
 M 14 / 22.2 mm

 Power:
 1,750 Watt
 Weight:
 3.9 kg

 Speed:
 1,700 - 6,800 rpm
 Soft start,

Tool Ø max.: 150 mm Overload protection

Cutting depth max. 40 mm

Included:

Silicone connecting cable 4 m, vacuum cleaner connection rotatable Ø 36-46 mm, removable guide plate with connection to guide rail, plastic coating with velcro, stopper plate, flange, FIXTEC flange nut, ball handle, case.

Available versions: SMART CUTTER 1700 Vario Plus

GALESKI - Manufaktur innovativer Maschinen Boschstr. 4 • D-56457 Westerburg

230V

Tel.: +49 2663 9437-0 • Fax: +49 2663-9437-37 E-Mail: info@galeski.de • Web: www.galeski.de

Item no.: 003.036.607



Application 1:

guide edge

- freehand cut without guide plate
- right-angle cut in stone (pivot in with the guide plate)

guide plate

- pulling cut
- with dust extraction.



Application 2:

- with guide plate
- depth of cut adjustment is variable
- pulling cut
- with dust extraction.



Application 3:

- with guide plate
- depth of cut adjustment is variable
- pulling cut
- with dust extraction.



Application 4:

- with guide plate
- use with GALESKI rail system for exact cuts
- pulling cut
- with dust extraction.

