



For a long service life, the machine body is fitted with a flexible plastic splash guard.



An easily removable cover that can be removed without tools.



Large clamping flange:

- gives additional stability. The cut-off wheel has less tendency to "vibrate".
- causes the cooling water to be thrown away in wet operation. An additional protection against water penetration.

Brief description:

Rugged stone cutter with high power reserves for continuous use.

Special features:

- The water supply takes place via an individually adjustable articulated hose with a preset water nozzle.
- A water regulating valve ensures a finely adjustable water quantity regulation.
- An easily removable cover sits in front of the protective cover. This can be easily removed when replacing the cutting wheel with only one star knob screw without tools.
- Proven, flexible and transparent splash guard. This means that less moisture and dirt is sucked into the engine compartment. This significantly increases the service life of the machine.
- Spindle lock for easy tool changes.
- Line lock out function to prevent automatic start up after power loss.
- Soft start for smooth start up.
- Protective hood adjustment at the push of a button. Rotating handle adjustable in 7 positions
- Speed designed for stone cutting.
- Special requests (e.g. for longer connecting cables or hoses) can be considered.
- Repair service for all of our machines.

Application:

Dry stone cutter for natural or artificial stone processing. Especially suitable for stonemasons, sculptors, restorers, tilers, renovators, floor renovators, etc.

Technical Data:

Voltage:	230 Volt	Spindle thread:	M 14 / Ø 22.2 mm
Power:	2,400 Watt	Weight:	7.4 kg
Speed:	6,600 rpm	Soft start	
Tool Ø max.:	230 mm		
Cutting depth max.	63 mm		

Included:

Silicone connecting cable 4 m, personal protection switch PRCD or CEE-plug, hose 2.5 m with brass coupling, water control valve, jointed coolant hose, adjustable safety cover with removable front cover, flange and flange nut, twin hole wrench, socket wrench Ø 6mm, bail handle, splash guard, carton.

Available versions:

SMART CUTTER 230/2 Con CEE (for transformer) 230V	Item no.: 003.036.648
SMART CUTTER 230/2 Con DI (with PRCD) 230V	Item no.: 003.036.649